
ZD350 Ultra (Dual head)



Dual cutter head configuration for cutting and creasing







Sutable for packaging box. origami indentation



Suitable for all kinds of material cutting

Head office address: 130,1st Floor, Downtown Mall, Lakadika Pul, Hyderabad, Telangana-500004. Braches: Kolkata, Banglore, Chennai, Calicut www.equipioindia.com | +91 99461 56516 | +91 95261 15411

Technical parameters:



Model	ZD350 Ultra (Dual head)	
Max media width	360mm	
Max cutting width	350mm	
Auto feeding quantity	150PCS	
Cutting thickness	350g Cut through	
Motor	Servo	
Cutting speed	1600mm/s	
Maximum standby running speed	1600mm/s	
Positioning	HD camera automatic positioning	
Cutting force	2000g	
Blade	Double cutter head (one side cutting, one side indentation)	
Interface	U disc/USB/WIFI(Optional)	
Accuracy	+/-0.1mm	
Repeat/Positioning precision	+/-0.082mm	
Working environment	5°C-35°C	
OS/Software	Windows XP 7/8/10 CoreIDAW/Illustrator/Camera Cut	
Cuttable material	All kinds of packaging proofing, labels, paper cards, self-adhesive, etc	
Product size	770*455*350mm	
Packing size	870*550*570mm	











Label

Drop

Heat transfer printing Stickers and decals

Packing box



MKC Series

Fully automatic digital Printing die-cutting

MKC series products adopt automatic feeding and receiving methods, which can realize "5 automatic Automatic", that is, automatic feeding, automatic calling of cutting files, automatic positioning, automatic Automatic cutting and automatic

material collection can realize one person to control multiple devices, reduce work intensity, save labor costs, and improve work efficiency

Equipped with high-definition CCD camera

Realize automatic and precise positioning of various materials, with high precision and reduce errors.



All-in-one design

The whole adopts an integrated structure, and the operation is more stable

Equipped with various tools

Realize the arbitrary switching of tools, cutting multiple materials

Imported rail

Using Taiwan's upper silver guide rail, higher precision.

Simple software operation

One-button operation, no complicated settings.

Head office address: 130,1st Floor, Downtown Mall, Lakadika Pul, Hyderabad, Telangana-500004.

Braches: Kolkata, Banglore, Chennai, Calicut

www.equipioindia.com | +91 99461 56516 | +91 95261 15411

Technical Parameters



Model	MKC-0806	MKC-1209	
Air pump power	2.2KW	4.4KW	
Total rated power	5.5KW	9.5KW	
Effective working range	800*600mm	1200*900mm	
Overall size	3600*1180*1270mm	4700*1460*1270mm	
Cutting materials	Stickers, cardboard, PP paper, labels, all kinds of corrugated cardboard, yellow thick cardboard, red cardboard, honeycomb board, etc.		
Working Characteristics	Can be connected to any CAD software, computer-aided design and cutting at the same time		
Standard tools	Creasing wheel, graphtec tool, Neutral Pen Holder, Rotary kiss-cut tool, Cursor, CCD camera		
Optional tools	Mini oscillating tool, V-Cut tool, Mini universal cutting tool		
Cutting thickness	≤10MM (according to different cutting materials)		
Cutting speed	300-1200mm/s		
Fixing method	Vacuum adsorption (with backdraft)		
Repeat accuracy	≤0.01mm		
Software resolution	0.025		
Transmission port	Standard network port		
Buffer capacity	One-time fast transfer of page changeable cuts		
File system	HPGL-compatible format		
User interface	Touchscreen		
Driveline	High-end servo motor drive, linear guide		
Operating Voltage/Power	AC 220V/380V±10%50HZ		
Working environment	Temperature: 0° ~ 35° Humidity: 35% ~ 80%		

^{*}The company reserves the right of final interpretation of the above parameters, subject to change without notice

Function and application industry

Various corrugated cardboard, plastic board, yellow cardboard, red cardboard, white cardboard, gray cardboard, PVC board, foam board, EVA board, KT board, self-adhesive, gasket etc

